

**LEGEND:**

**GR:** Powder Coated Supr-Green **EG:** Electro-Galvanized **PG:** Pre-Galvanized **AL:** Aluminum **HG:** Hot Dipped Galvanized **PL:** Plain **SS:** Stainless Steel **ZTC:** Zinc Trivalent Chromium  
 For Zinc Trivalent Chromium (ZTC), refer to pages 82-88 in the Specialty Strut Section. For Load Rating, see page 94.

**AS 3025 GR, EG**

**POST BASE**

Use With AS 200 and AS 210.

6 Holes  $\frac{9}{16}$ " Dia.

2 Holes  $\frac{3}{4}$ " Dia.

Std Pkg: 10 · Wt./100 pcs: 358 lbs.

**AS 3025 FL GR, EG**

**POST BASE**

Use With AS 200 and AS 210.

6 Holes  $\frac{9}{16}$ " Dia.

2 Holes  $\frac{3}{4}$ " Dia.

Std Pkg: 10 · Wt./100 pcs: 312 lbs.

**AS 3029 GR, EG**

**DOUBLE COLUMN POST BASE**

Use With All  $3\frac{1}{4}$ " Channels  
 Square Alternative also offered.

4 Holes  $\frac{9}{16}$ " Dia.

4 Holes  $\frac{3}{4}$ " Dia.

Std Pkg: 5 · Wt./100 pcs: 325 lbs.

**AS 3033 GR, EG, ZTC**

**POST BASE**

Use With AS 200 and AS 210.

6 Holes  $\frac{9}{16}$ " Dia.

4 Holes  $\frac{3}{4}$ " Dia.

Std Pkg: 10 · Wt./100 pcs: 373 lbs.

**AS 3040 GR, EG**

**POST BASE**

Use With AS 200 and AS 210.

4 Holes  $\frac{7}{16}$ " Dia.

Std Pkg: 10 · Wt./100 pcs: 297 lbs.

**AS 3064 GR, EG, ZTC**

**DOUBLE COLUMN POST BASE**

Use With All  $3\frac{1}{4}$ " Channels.  
 Flush Alternative also offered.

8 Holes  $\frac{9}{16}$ " Dia.

4 Holes  $\frac{3}{4}$ " Dia.

Std Pkg: 10 · Wt./100 pcs: 408 lbs.