

LEGEND:

GR: Powder Coated Supr-Green **EG:** Electro-Galvanized **PG:** Pre-Galvanized **AL:** Aluminum **HG:** Hot Dipped Galvanized **PL:** Plain **SS:** Stainless Steel **ZTC:** Zinc Trivalent Chromium
 For Zinc Trivalent Chromium (ZTC), refer to pages 82-88 in the Specialty Strut Section. For Load Rating, see page 94.

AS 612 GR, EG

"Z" SUPPORT

Use With AS 400.

A = 1"

Std Pkg: 50 · Wt./100 pcs: 47 lbs.

AS 613 GR, EG, ZTC

"U" SUPPORT

Use With AS 200, AS 210, and AS 500BTB.

A = 1 5/8"

Std Pkg: 25 · Wt./100 pcs: 88 lbs.

AS 614 GR, EG

FOUR HOLE JOINT ANGLE CONNECTOR

Std Pkg: 25 · Wt./100 pcs: 103 lbs.

AS 615 GR, EG

FIVE HOLE SHELF JOINT ANGLE CONNECTOR

Std Pkg: 10 · Wt./100 pcs: 135 lbs.

AS 616 GR, EG, ZTC

FOUR HOLE SPLICE CLEVIS

Use With AS 200 and AS 210.

Std Pkg: 10 · Wt./100 pcs: 265 lbs.

AS 617 GR, EG

THREE HOLE SWIVEL PLATE

Std Pkg: 25 · Wt./100 pcs: 75 lbs.

AS 619 GR, EG, SS, ZTC

SQUARE WASHER

Bolt Size "A"

A	Wt./100 pcs
1/4"	18
3/8"	18
1/2"	17
5/8"	16
3/4"	15
7/8"	-

Std Pkg: 100 · Wt./100 pcs: See chart above.

AS 620 GR, EG

TWO HOLE CONNECTING PLATE

Holes C to C
1 5/8"

Std Pkg: 50 · Wt./100 pcs: 35 lbs.