



# Malleable Iron


Class 300 (XS / XH)

| FIGURE 1163<br>Cap  | Size  |    | Height<br>L |    | Unit Weight |      |       |      |
|---|-------|----|-------------|----|-------------|------|-------|------|
|   |       |    |             |    | Black       |      | Galv. |      |
|   | NPS   | DN | in          | mm | lbs         | kg   | lbs   | kg   |
|  | 1/4   | 8  | 25/32       | 20 | 0.10        | 0.05 | 0.10  | 0.05 |
|   | 3/8   | 10 | 13/16       | 22 | 0.15        | 0.07 | 0.15  | 0.07 |
|   | 1/2   | 15 | 1           | 25 | 0.23        | 0.10 | 0.23  | 0.10 |
|   | 3/4   | 20 | 1 1/16      | 27 | 0.35        | 0.16 | 0.35  | 0.16 |
|   | 1     | 25 | 1 1/4       | 32 | 0.58        | 0.26 | 0.58  | 0.26 |
|   | 1 1/4 | 32 | 1 3/8       | 35 | 1.00        | 0.45 | 1.00  | 0.45 |
|   | 1 1/2 | 40 | 1 7/16      | 37 | 1.18        | 0.54 | 1.18  | 0.54 |
|   | 2     | 50 | 1 11/16     | 43 | 1.94        | 0.88 | 1.94  | 0.88 |
|   | 2 1/2 | 65 | 2 1/16      | 52 | 3.32        | 1.51 | 3.32  | 1.51 |
|   | 3     | 80 | 2 3/16      | 56 | 4.71        | 2.14 | 4.71  | 2.14 |

| FIGURE 390<br>Square Countersunk Plugs   | Size |    | Unit Weight |      |       |      |
|--|------|----|-------------|------|-------|------|
|  |      |    | Black       |      | Galv. |      |
|  | NPS  | DN | lbs         | kg   | lbs   | kg   |
|  | 1/2  | 15 | 0.05        | 0.02 | 0.05  | 0.02 |
|  | 3/4  | 20 | 0.11        | 0.05 | 0.11  | 0.05 |

See page 52 (Cast Iron) for other available sizes.

# All Iron Unions

| FIGURE J-3300<br>All Iron Union Class 300   | Size  |    | End to End |     | Unit Weight |      |
|---|-------|----|------------|-----|-------------|------|
|   |       |    |            |     | Black       |      |
|   | NPS   | DN | in         | mm  | lbs         | kg   |
|  | 1/4   | 8  | 1 5/8      | 41  | 0.27        | 0.12 |
|   | 3/8   | 10 | 1 13/16    | 47  | 0.37        | 0.17 |
|   | 1/2   | 15 | 2 1/8      | 54  | 0.51        | 0.23 |
|   | 3/4   | 20 | 2 7/16     | 62  | 0.76        | 0.34 |
|   | 1     | 25 | 2 3/4      | 70  | 1.20        | 0.54 |
|   | 1 1/4 | 32 | 3          | 76  | 1.87        | 0.85 |
|   | 1 1/2 | 40 | 3 3/16     | 81  | 2.51        | 1.14 |
|   | 2     | 50 | 3 1/2      | 89  | 4.30        | 1.95 |
|   | 2 1/2 | 65 | 3 11/16    | 94  | 6.02        | 2.73 |
|   | 3     | 80 | 3 15/16    | 100 | 7.96        | 3.61 |

**Note:** See page 17 for pressure-temperature ratings. Galvanized weights may vary. Please contact your Anvil Representative if you need verification. All Elbows & Tees 3/4" (10 DN) and Larger are 100% Gas Tested at a Minimum of 100 PSI. (6.9 bar)