



Special Application Gauges
Type 1150H, ASME B 40.1 Grade 2A ($\pm 0.5\%$ of span)
Type 1122, ASME B 40.1 Grade A ($\pm 2-1-2\%$ of span)

1150H Reid Vapor Test Gauge

- Accuracy ASME B 40.1 Grade 2A ($\pm 0.5\%$ of span)
- Dial size 4½" only
- White dial and black pointer

The Ashcroft® Type 1150H is a specialized pressure gauge used by the petroleum industry to measure vapor pressures of various petroleum products.

1122KE/KF

- Accuracy ASME B 40.1 Grade A ($\pm 2-1-2\%$ of span)
- Dial size 2½" only

The Ashcroft® Type 1122 is a specialized product used for some pump, turbine and compressor applications.



SPECIFICATIONS

Gauge Type Number	Dial Size (Inches)	Case & Ring Material Finish	Bourdon Tube & Tip Material (all joints welded)	Socket Material	Pressure Range (psi)	Pointer	Movement	NPT Conn.
Reid Vapor Test 1150H	4½"	Case: Aluminum Ring: Threaded Aluminum black epoxy coated	Phosphor Bronze Tip: Brass (All joints silver brazed)	Brass	15/600	Micrometer Adjustable	Stainless steel Teflon coated, pinion and sector shaft, rotary geared	¼"
1122KE ⁽¹⁾ 1122KF	2½"	Case: Stainless steel Ring: Bayonet Lock, St.St. Both polished	Phosphor Bronze Tip: Brass (All joints silver brazed)	Brass	15/1000	Non adjustable	Stainless steel	¼"

TYPE 1150H			
Range		Dial Graduations	
kg/cm ² kilograms per sq. cm.	bar	Major Interval	Minor Graduation
0/1	0/1	0.1	0.01
0/1.6	1.6	0.2	0.02
0/2.5	2.5	0.5	0.05
0/4	0/4	0.5	0.05
0/6	0/6	0.5	0.1
0/10	0/10	1	0.1
0/16	0/16	2	0.2
0/25	0/25	5	0.5
0/40	0/40	5	0.5

TYPE 1150H		
Range	Dial Graduations	
kPa (kilopascal)	Major Interval	Minor Graduation
0/100	10	1
0/160	20	2
0/250	50	5
0/400	50	5
0/600	50	10
0/1000	100	10
0/1600	200	20
0/2500	500	50
0/4000	500	50

TYPE 1122			
Range		Dial Graduations	
kg/cm ² kilograms per sq. cm.	bar	Major Interval	Minor Graduation
0/1	0/1	0.1	0.01
0/1.6	0/1.6	0.2	0.02
0/2.5	0/2.5	0.5	0.05
0/4	0/4	0.5	0.05
0/6	0/6	0.5	0.1
0/10	0/10	1	0.1
0/16	0/16	2	0.2
0/25	0/25	5	0.5
0/40	0/40	5	0.5
0/60	0/60	5	1

Compound			
Range	Dial Graduations		
kPa (kilopascal)	Major Interval	Minor Graduation	Dual-Scale psi
0/100	10	1	0/14
0/160	20	2	0/22
0/250	50	5	0/35
0/400	50	5	0/55
0/600	50	10	0/85
0/1000	100	10	0/140
0/1600	200	20	0/220
0/2500	500	50	0/350
0/4000	500	50	0/550
0/6000	500	100	0/850

Compound			
Range	Dial Graduations		
psi	Major Interval	Minor Graduation	Dual-Scale psi
-100/0/300	50	5	30"Hg/40
-100/0/500	50	50	30"Hg/70

STANDARD RANGES		
Range psi	Major Interval	Minor Graduation
Type 1150H		
0/15	1	0.1
0/30	2	0.2
0/45	3	0.2
0/60	4	0.25
0/100	5	0.5
0/200	10	1
0/250	10	1
0/300	10	2
0/600	20	2
Type 1122 (60° dial arc except 15psi-45°)		
0/15	5	1
0/30	10	2
0/60	15	5
0/100	20	10
0/160	40	10
0/200	50	10
0/300	100	25
0/400	100	25
0/600	150	50
0/1000	250	50

(1) The 1122KE is stem mounted.
 The 1122KF is surface mounted with a back flange.

TO ORDER THESE 1150H & 1122 GAUGES:

Select: _____ 45 _____ 1150 _____ H _____ 02L _____ XXX _____ 600#

1. Dial size—2½", 4½" _____

2. Type _____

3. Tube and socket material—see chart above _____

4. Connection size—¼ (02) _____

5. Connection location—Lower (L) only _____

6. Optional features—see page 249 _____

7. Standard pressure range 600 psi _____

Accessories—see pages 243-248

Consult factory for guidance in product selection
 Phone (203) 385-0217, Fax (203) 385-0602 or
 visit our web site at www.ashcroft.com