

**LEGEND:**

**GR:** Powder Coated Supr-Green **EG:** Electro-Galvanized **PG:** Pre-Galvanized **AL:** Aluminum **HG:** Hot Dipped Galvanized **PL:** Plain **SS:** Stainless Steel **ZTC:** Zinc Trivalent Chromium  
 For Zinc Trivalent Chromium (ZTC), refer to pages 82-88 in the Specialty Strut Section. For Load Rating, see page 94.

**AS 687** GR, EG, ZTC

**SLOTTED "U" SUPPORT**

Use With AS 200 and AS 210.

	A	C to C	Wt/100 pcs
A	7 <sup>1</sup> / <sub>4</sub> "	4 <sup>1</sup> / <sub>8</sub> "	105
B	8 <sup>1</sup> / <sub>2</sub> "	5 <sup>7</sup> / <sub>8</sub> "	120
C	10 <sup>3</sup> / <sub>8</sub> "	7 <sup>1</sup> / <sub>4</sub> "	130

Std Pkg: 10  
 Wt/100 pcs: See chart above.

**AS 689** GR, EG, ZTC

**ADJUSTABLE DOUBLE SLOTTED CORNER CONNECTOR**

	A	C to C	Wt/100 pcs
A	6 <sup>5</sup> / <sub>8</sub> "	4"	190
B	8 <sup>5</sup> / <sub>8</sub> "	6"	242

Std Pkg: 10 · Wt/100 pcs: See chart above.

**AS 708** GR, EG

**SINGLE CHANNEL BRACKET SUPPORT**

Use With AS 200, AS 210 and AS 500BTB.

Std Pkg: 20 · Wt/100 pcs: 235 lbs.

**AS 710** GR, EG

**"U" SUPPORT**

Use With AS 300.

A = 1<sup>1</sup>/<sub>8</sub>"

Std Pkg: 25 · Wt/84 pcs: 38 lbs.

**AS 711** GR, EG

**"Z" SUPPORT**

Use With AS 300.

A = 1<sup>1</sup>/<sub>8</sub>"

Std Pkg: 25 · Wt/100 pcs: 53 lbs.

**AS 712** GR, EG, ZTC

**CROSS PLATE**

Std Pkg: 10 · Wt/100 pcs: 105 lbs.

**AS 714** GR, EG, ZTC

**"T" PLATE**

Std Pkg: 25 · Wt/100 pcs: 80 lbs.

**AS 715** GR, EG

**"T" PLATE 90° ANGLE**

Std Pkg: 20 · Wt/100 pcs: 71 lbs.