

LEGEND:

GR: Powder Coated Supr-Green **EG:** Electro-Galvanized **PG:** Pre-Galvanized **AL:** Aluminum **HG:** Hot Dipped Galvanized **PL:** Plain **SS:** Stainless Steel **ZTC:** Zinc Trivalent Chromium
 For Zinc Trivalent Chromium (ZTC), refer to pages 82-88 in the Specialty Strut Section. For Load Rating, see page 94.

AS 687 GR, EG, ZTC

SLOTTED "U" SUPPORT

Use With AS 200 and AS 210.

	A	C to C	Wt/100 pcs
A	7 ¹ / ₄ "	4 ¹ / ₈ "	105
B	8 ¹ / ₂ "	5 ⁷ / ₈ "	120
C	10 ³ / ₈ "	7 ¹ / ₄ "	130

Std Pkg: 10
 Wt/100 pcs: See chart above.

AS 689 GR, EG, ZTC

ADJUSTABLE DOUBLE SLOTTED CORNER CONNECTOR

	A	C to C	Wt/100 pcs
A	6 ⁵ / ₈ "	4"	190
B	8 ⁵ / ₈ "	6"	242

Std Pkg: 10 · Wt/100 pcs: See chart above.

AS 708 GR, EG

SINGLE CHANNEL BRACKET SUPPORT

Use With AS 200, AS 210 and AS 500BTB.

Std Pkg: 20 · Wt/100 pcs: 235 lbs.

AS 710 GR, EG

"U" SUPPORT

Use With AS 300.

A = 1¹/₈"

Std Pkg: 25 · Wt/84 pcs: 38 lbs.

AS 711 GR, EG

"Z" SUPPORT

Use With AS 300.

A = 1³/₈"

Std Pkg: 25 · Wt/100 pcs: 53 lbs.

AS 712 GR, EG, ZTC

CROSS PLATE

Std Pkg: 10 · Wt/100 pcs: 105 lbs.

AS 714 GR, EG, ZTC

"T" PLATE

Std Pkg: 25 · Wt/100 pcs: 80 lbs.

AS 715 GR, EG

"T" PLATE 90° ANGLE

Std Pkg: 20 · Wt/100 pcs: 71 lbs.