


Clamps

Service pressure ratings are based on the following parameters: matching elastomer gaskets and weld ferrules properly aligned and assembled with the clamps tightened to the required torques. Tests are done hydrostatically with no water hammer or shock loads. Please note the pressure ratings of the described unions may be above the recommended pipe line operating pressures. SAFETY
ALFR

Single Pin Squeeze Clamps - 13MHHM-Q



Tube OD	Service Pressure Rating @ 70°F *	Service Pressure Rating @ 250°F *	A	Part Number
½" - ¾"	1500	1200	1.062	13MHHM-Q75
1" - 1½"	500	300	2.122	13MHHM-Q100150
2"	450	250	2.654	13MHHM-Q200
2½"	400	200	3.185	13MHHM-Q250
3"	350	175	3.717	13MHHM-Q300
4"	300	150	4.820	13MHHM-Q400

* wing nut tightened to 25 in. lb. of torque



Tale of Two Clamps video

Scan me with your Smart Phone. No reader? Download a free QR-Code 2D barcode reader. <http://www.mobile-barcodes.com/qr-code-software/>


Single Pin Heavy Duty Clamps with Cross Hole Wing Nut - 13MHHM



Tube OD	Service Pressure Rating @ 70°F *	Service Pressure Rating @ 250°F *	A	Part Number
½" - ¾"	1500	1200	1.062	13MHHM50-75
1" - 1½"	500	300	2.122	13MHHM100-150
2"	450	250	2.654	13MHHM200
2½"	400	200	3.185	13MHHM250
3"	350	175	3.717	13MHHM300
4"	300	150	4.820	13MHHM400
5"	225	100	5.820	13MHHM500
6"	150	75	6.695	13MHHM600
8"	100	50	8.695	13MHHM800

* wing nut tightened to 25 in. lb. of torque

Single Pin Heavy Duty Clamps with Serrated Wing Nut - 13MHHM***SN



Tube OD	Service Pressure Rating @ 70°F *	Service Pressure Rating @ 250°F *	A	Part Number
½" - ¾"	1500	1200	1.062	13MHHM50-75SN
1" - 1½"	500	300	2.122	13MHHM100-150SN
2"	450	250	2.654	13MHHM200SN
2½"	400	200	3.185	13MHHM250SN
3"	350	175	3.717	13MHHM300SN
4"	300	150	4.820	13MHHM400SN
5"	225	100	5.820	13MHHM500SN
6"	150	75	6.695	13MHHM600SN
8"	100	50	8.695	13MHHM800SN

* wing nut tightened to 25 in. lb. of torque

Double Pin Heavy Duty Clamps - 13MHHM-DP



Tube OD	Service Pressure Rating @ 70°F *	Service Pressure Rating @ 250°F *	A	Part Number
1" - 1½"	500	300	2.122	13MHHM-DP100150
2"	450	250	2.654	13MHHM-DP200
2½"	400	200	3.185	13MHHM-DP250
3"	350	175	3.717	13MHHM-DP300
4"	300	150	4.820	13MHHM-DP400
10"	100	50	10.740	13MHHM-DP1000

* wing nut tightened to 25 in. lb. of torque