

LEGEND:

GR: Powder Coated Supr-Green **EG:** Electro-Galvanized **PG:** Pre-Galvanized **AL:** Aluminum **HG:** Hot Dipped Galvanized **PL:** Plain **SS:** Stainless Steel **ZTC:** Zinc Trivalent Chromium
 For Stainless Steel (SS) and Zinc Trivalent Chromium (ZTC), refer to pages 86 and 87 in the Specialty Strut Section.

AS 3126 EG

HOLD DOWN CLAMP

Size	A	Std Pkg	Wt/100 pcs
1/2"	2 7/8"	50	23
3/4"	3 1/16"	50	26
1"	3 1/32"	25	31
1 1/4"	3 1/16"	25	35
1 1/2"	3 29/32"	25	39
2"	5 21/32"	25	94
2 1/2"	6 3/32"	25	114
3"	6 25/32"	25	133
3 1/2"	7 1/32"	10	152
4"	7 25/32"	Bulk	176
5"	7 27/32"	Bulk	198
6"	9 29/32"	Bulk	225

Size	B	C	D
1/2 - 1 1/2"	1/8"	9/32"	7/16"
2 - 6"	1/4"	13/32"	13/16"

Nominal Pipe Size	Design Loads (Safety Factor 3.0)		
	Pullout (lbs)	Slip Along (lbs)	Slip Thru (lbs)
1/2"	811	479	425
3/4"	850	405	184
1	769	455	168
1 1/4"	830	401	402
1 1/2"	876	532	315
2"	2,133	1,728	553
2 1/2"	2,280	1,615	408
3	2,295	1,494	900
3 1/2"	2,273	1,516	646
4"	2,324	1,463	834
5"	2,324	1,097	564
6"	2,250	899	494

Std Pkg & Wt/100 pcs: See chart above.

AS 3138 EG

PARALLEL PIPE CLAMP

Size	Load Rating (lbs)	Std Pkg	Wt/100 pcs
3/8"	300	50	27
1/2"	300	50	29
3/4"	300	50	30
1"	400	50	31
1 1/4"	400	50	38
1 1/2"	500	50	40
2"	500	25	47
2 1/2"	500	25	66
3"	500	25	78
3 1/2"	500	25	87
4"	500	25	90

Std Pkg & Wt/100 pcs: See chart above.

AS 3792 EPDM

CUSHION STRIP

lock-lip edge
 compression ribs

Material: EPDM
 Service Temperature -50°F to 275°F.

Std Pkg: 20 Ft./Box · Wt/100 boxes: 253 lbs.