

# 90° ELBOW



## Cast Iron - Class 125 Fittings




### MATERIAL SPECIFICATIONS

Cast iron threaded fittings are UL & ULC Listed and FM Approved.

Cast iron per ASTM A126.

Dimensions conform to ANSI B16.4 Class 125.

Threads are NPT per ANSI/ASME B1.20.1.




For Listings/Approval Details and Limitations, visit our website at [www.anvilintl.com](http://www.anvilintl.com) or contact an Anvil® Sales Representative.

### 90° ELBOW

Nominal Size	Max. Working Pressure▲	Dimensions		Approx. Wt. Each
		A	B	
<i>In. (mm)</i>	<i>PSI (kPa)</i>	<i>In. (mm)</i>	<i>In. (mm)</i>	<i>Lbs. (kg)</i>
1 25	300 2065	1.50 38.10	1.50 38.10	0.84 0.38
1¼ 32	300 2065	1.75 44.45	1.75 44.45	1.34 0.61
1½ 40	300 2065	1.94 49.27	1.94 49.27	1.80 0.82
2 50	300 2065	2.25 57.15	2.25 57.15	2.90 1.32
2½ 65	300 2065	2.70 68.58	2.70 68.58	4.75 2.15

▲ – Working Pressure Ratings are for reference only and based on Sch. 40 pipe. For the latest UL/ULC, and FM pressure ratings versus pipe schedule, please visit [anvilintl.com](http://anvilintl.com) or contact your local Anvil Representative.





[www.anviltl.com](http://www.anviltl.com)

REV. 4.5.12 - 1