



## Cast Iron - Class 125 Fittings




### MATERIAL SPECIFICATIONS

Cast iron threaded fittings are UL & ULC Listed and FM Approved.

Cast iron per ASTM A126.

Dimensions conform to ANSI B16.4 Class 125.


Threads are NPT per ANSI/ASME B1.20.1.



For Listings/Approval Details and Limitations, visit our website at [www.anvilintl.com](http://www.anvilintl.com) or contact an Anvil® Sales Representative.

### CROSS

Nominal Size	Max. Working Pressure▲	Dimensions		Approx. Wt. Each
		A	B	
<i>In. (mm)</i>	<i>PSI (kPa)</i>	<i>In. (mm)</i>	<i>In. (mm)</i>	<i>Lbs. (kg)</i>
1 25	300 2065	1.50 38.10	1.50 38.10	1.54 0.70
1¼ 32	300 2065	1.75 44.45	1.75 44.45	2.40 1.09
1½ 40	300 2065	1.94 49.276	1.94 49.27	3.10 1.41
2 50	300 2065	2.25 57.15	2.25 57.15	4.00 1.81
1¼ x 1 32 x 25	300 2065	1.58 40.13	1.67 42.41	2.05 0.93
1½ x 1 40 x 25	300 2065	1.65 41.91	1.80 45.72	2.40 1.09
2 x 1 50 x 25	300 2065	1.73 38.60	2.02 44.45	2.75 1.25



▲ - Working Pressure Ratings are for reference only and based on Sch. 40 pipe. For the latest UL/ULC, and FM pressure ratings versus pipe schedule, please visit [anvilintl.com](http://anvilintl.com) or contact your local Anvil Representative.



[www.anviltl.com](http://www.anviltl.com)

REV. 4.5.12 - 7