


Schedule 80 CPVC Technical
Schedule 80 CPVC Fittings



22-1/2° EII

Socket x Socket

(Continued)




Part Number	Size	H	J	M	Approx. Wt. (Lbs.)
816-025CF*	2-1/2	2- 7/8	7/8	3- 7/16	.81
816-030C	3	2-3/8	1/2	4- 5/32	1.00
816-040C	4	2- 7/8	5/8	5- 1/4	1.71
816-050CF*	5	4-1/8	1-1/8	6-5/16	3.22
816-060C	6	3-15/16	7/8	7- 9/16	4.59
816-060CF*	6	4- 5/8	1- 3/8	7- 1/2	5.16
816-080C	8	5- 1/16	1- 1/32	9- 3/4	8.59
816-080CF*	8	5- 7/8	1- 5/8	9- 5/8	9.36
816-100CF*	10	7- 5/16	2- 1/16	11-15/16	17.59
816-120CF*	12	8- 9/16	2- 5/16	14- 1/8	29.69
816-140CF*	14	9-13/16	2-13/16	15- 1/2	37.75
816-160CF*	16	11- 5/16	3- 5/16	17-11/16	57.95
816-180CF*	18	12- 3/4	3- 3/4	19- 7/8	86.42
816-200CF*	20	14-1/4	4-1/4	22-1/16	103.22
816-240CF*	24	17-3/16	5-3/16	26-7/16	205.70

* Fabricated

45° EII

Socket x Socket



Part Number	Size	H	J	M	Approx. Wt. (Lbs.)
817-002C	1/4	13/16	5/32	27/32	.02
817-003C	3/8	15/16	3/16	1	.03
817-005C	1/2	1-1/8	1/4	1-3/16	.06
817-007C	3/4	1-5/16	5/16	1-7/16	.09
817-010C	1	1-7/16	5/16	1-23/32	.16
817-012C	1-1/4	1-5/8	3/8	2-1/8	.22
817-015C	1-1/2	1-13/16	7/16	2-3/8	.29
817-020C	2	2-1/8	5/8	2-7/8	.47
817-025C	2-1/2	2-7/16	11/16	3-1/2	.82
817-030C	3	2-25/32	29/32	4-1/8	1.21
817-040C	4	3-5/16	1-1/16	5-1/4	2.14
817-050C	5	4	1-3/8	6-13/32	3.30
817-050CF*	5	4-7/8	1-7/8	6-5/16	3.85
817-060C	6	4-3/4	1-3/4	7-9/16	5.58




Schedule 80 CPVC Technical
Schedule 80 CPVC Fittings

45° EII

(Continued)

Socket x Socket




Part Number	Size	H	J	M	Approx. Wt. (Lbs.)
817-080C	8	6	2	9-3/4	10.64
817-100C	10	7-5/8	2-19/32	12-1/8	20.08
817-100CF*	10	8-11/16	3- 7/16	11-15/16	19.37
817-120C	12	9-3/16	3-1/8	14-9/32	32.86
817-120CF*	12	10- 1/8	3- 7/8	14- 1/8	32.40
817-140C	14	10-11/32	3- 5/16	15- 5/8	43.00
817-140CF*	14	11- 9/16	4- 9/16	15- 1/2	41.37
817-160CF*	16	13- 5/16	5- 5/16	17-11/16	64.66
817-180CF*	18	15	6	19- 7/8	88.48
817-200CF*	20	16- 3/4	6- 3/4	22- 1/16	124.66
817-240CF*	24	20- 3/16	8- 3/16	26- 7/16	207.66

* Fabricated

15° EII

Socket x Socket



Part Number	Size	H	J	M	Approx. Wt. (Lbs.)
818-005CF*	1/2	1-5/16	5/16	1-1/8	.13
818-007CF*	3/4	1-5/16	5/16	1-3/8	.08
818-010CF*	1	1-5/8	3/8	1-11/16	.15
818-012CF*	1-1/4	2	1/2	2-1/16	.25
818-015CF*	1-1/2	2	1/2	2-5/16	.26
818-020CF*	2	2- 5/16	9/16	2-13/16	.48
818-025CF*	2-1/2	2- 3/4	3/4	3- 7/16	.88
818-030CF*	3	3	3/4	4- 1/8	1.25
818-040CF*	4	3- 1/8	7/8	5- 3/16	1.79
818-050CF*	5	3-15/16	15/16	6-5/16	3.08
818-060CF*	6	4- 3/8	1- 1/8	7- 1/2	4.77
818-080CF*	8	5-1/2	1- 1/4	9- 5/8	8.81
818-100CF*	10	6-15/16	1-11/16	11-15/16	17.29
818-120CF*	12	8- 1/16	1-13/16	14- 1/8	27.73
818-140CF*	14	9- 5/16	2- 5/16	15- 1/2	40.74
818-160CF*	16	10-11/16	2-11/16	17-11/16	59.47