


Schedule 80 CPVC Technical
Schedule 80 CPVC Fittings



15° EII

Socket x Socket

(Continued)




Part Number	Size	H	J	M	Approx. Wt. (Lbs.)
818-180CF*	18	12- 1/16	3- 1/16	19- 7/8	83.44
818-200CF*	20	13-1/2	3-1/2	22-1/16	99.90
818-240CF*	24	16-1/4	4-1/4	26-7/16	202.28

* Fabricated

45° EII


Fipt x Fipt



Part Number	Size	H	J	M	Approx. Wt. (Lbs.)
819-002C	1/4	3/4	5/32	27/32	.03
819-003C	3/8	25/32	3/16	1	.03
819-005C	1/2	31/32	1/4	1- 3/16	.07
819-007C	3/4	1-1/32	5/16	1- 3/8	.07
819-010C	1	1- 7/32	5/16	1-11/16	.14
819-012C	1-1/4	1-3/8	3/8	2- 3/16	.25
819-015C	1-1/2	1-25/32	7/16	2- 1/2	.32
819-020C	2	1-11/16	5/8	3	.48
819-025C	2-1/2	2-1/16	1-1/16	3- 1/2	1.24
819-030C	3	2-23/32	1-7/32	4- 9/32	1.91
819-040C	4	3- 1/4	1-3/4	5- 1/4	3.33

45° EII - Special Reinforced

SR Fipt x SR Fipt - Stainless Steel Collar



Part Number	Size	H	J	M	Approx. Wt. (Lbs.)
819-005CSR	1/2	1	5/16	1- 3/16	.09
819-007CSR	3/4	1- 1/8	13/32	1- 3/8	.11
819-010CSR	1	1- 1/4	13/32	1-23/32	.17