


Schedule 80 CPVC Technical
Schedule 80 CPVC Fittings



Plug
 Spigot


(Continued)



Part Number	Size	L	Approx. Wt. (Lbs.)
849-015C	1-1/2	1-11/16	.14
849-020C	2	1- 7/8	.22
849-025CF ^{4*}	2-1/2	5- 3/8	1.12
849-030CF ^{4*}	3	5-7/8	1.55
849-040CF ^{4*}	4	6-15/16	2.66
849-060CF ^{4*}	6	9-5/8	6.75
849-080CF ^{4*}	8	12-3/16	13.50
849-100CF ^{4*}	10	12-1/4	17.99
849-120CF ^{4*}	12	14-1/8	28.85
849-140CF ^{4*}	14	15-3/8	39.91
849-160CF ^{4*}	16	18	57.90
849-180CF ^{4*}	18	19-1/4	74.02
849-200CF ^{4*}	20	25-1/4	76.91
849-240CF ^{4*}	24	30-1/4	208.48

⁴ Plug fabricated using Cap and pipe spigot.
 * Fabricated

Plug
 Mipt




Part Number	Size	L	Approx. Wt. (Lbs.)
850-002C	1/4	23/32	.01
850-003C	3/8	3/4	.01
850-005C	1/2	27/32	.01
850-007C	3/4	7/8	.02
850-010C	1	1- 1/16	.05
850-012C	1-1/4	1-5/16	.07
850-015C	1-1/2	1-3/8	.10
850-020C	2	1- 3/8	.16
850-025C	2-1/2	1-13/16	.29
850-030C	3	1- 7/8	.45
850-040C	4	2-1/8	.81
850-060C	6	2- 3/32	1.79
850-060CF ^{4*}	6	7-1/2	5.50
850-080C	8	2-13/32	3.53



Schedule 80 CPVC Technical
Schedule 80 CPVC Fittings

Plug
 Mipt

(Continued)




Part Number	Size	L	Approx. Wt. (Lbs.)
850-080CF ^{4*}	8	9-11/16	12.18
850-100CF ^{4*}	10	8- 7/16	13.76
850-120CF ^{4*}	12	10-5/8	24.34

⁴ Plug fabricated using Cap and threaded pipe.
 * Fabricated

Wye

Socket x Socket
 1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 8" - 10" & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 12" 80 psi Maximum Internal Pressure Rating @ 73°F (23°C)



Part Number	Size	G	G1	G2	H	H1	H2	L	M	M1	Approx. Wt. (Lbs.)
875-005C	1/2	1/4	1-3/16	1-3/16	1-5/32	2- 1/16	2-1/16	3-7/32	1- 5/32	1- 5/32	.12
875-007C	3/4	9/32	1-13/32	1-13/32	1-9/32	2-13/32	2-13/32	3-11/16	1- 3/8	1- 3/8	.19
875-010C	1	11/32	1- 3/4	1- 3/4	1-15/32	2-7/8	2- 7/8	4-11/32	1-11/16	1-11/16	.32
875-012C	1-1/4	13/32	2-3/16	2-3/16	1-21/32	3-15/32	3-15/32	5-1/8	2- 1/16	2- 1/16	.52
875-015C	1-1/2	15/32	2-19/32	2-19/32	1-27/32	3-31/32	3-31/32	5-13/16	2-11/32	2-11/32	.73
875-020C	2	5/8	3- 7/32	3- 7/32	2- 5/32	4-23/32	4-23/32	6- 7/8	2- 7/8	2- 7/8	1.27
875-025C	2-1/2	27/32	3-31/32	3-31/32	2-19/32	5-23/32	5-23/32	8- 5/16	3- 1/2	3- 1/2	2.04
875-030C	3	31/32	4- 3/4	4-3/4	2-7/8	6- 5/8	6-5/8	9- 1/2	4- 3/16	4- 3/16	3.12
875-040C	4	1-7/32	6- 1/32	6- 1/32	3-15/32	8- 9/32	8- 9/32	11-3/4	5- 1/4	5- 1/4	5.35
875-060C	6	1-13/32	8-21/32	8-1/16	4-13/32	11-21/32	11-1/16	15-15/32	7- 9/16	7- 9/16	13.21
875-080C	8	2-1/32	11-9/32	11-9/32	6-1/32	15-9/32	15-9/32	21- 5/16	9- 3/4	9- 3/4	28.12
875-080CF ^{2*}	8	5- 1/16	15- 7/8	13-11/16	9- 5/16	20- 1/8	17-15/16	27- 1/4	9- 5/8	9- 5/8	37.70
875-100CF ^{2*}	10	6- 1/2	18- 7/8	17- 1/4	11- 3/4	24- 1/8	22- 1/2	34- 1/4	11-15/16	11-15/16	73.03
875-120CF ^{2*}	12	7- 1/8	21-13/16	19- 7/8	13- 3/8	28- 1/16	26- 1/8	39- 1/2	14- 1/8	14- 1/8	111.12
875-140CF ^{2*}	14	9-13/16	23-13/16	23-13/16	16-13/16	30-13/16	30-13/16	47- 5/8	15- 1/2	15- 1/2	159.14
875-160CF ^{2*}	16	10- 1/8	26- 1/8	26- 1/8	18- 1/8	34- 1/8	34- 1/8	52- 1/4	17-11/16	17-11/16	211.72
875-180CF ^{2*}	18	10	29- 3/8	28	19	38- 3/8	37	56	19- 7/8	19- 7/8	292.03
875-200CF ^{2*}	20	11-5/8	31-5/8	31-5/8	21-5/8	41-5/8	41-5/8	63-1/4	22-1/16	22-1/16	374.67
875-240CF ^{2*}	24	14-1/4	38-1/4	38-1/4	26-1/4	50-1/4	50-1/4	76-1/2	26-7/16	26-7/16	719.95

² Fiberglass reinforced.
 * Fabricated