


Schedule 80 CPVC Technical
Schedule 80 CPVC Fittings



90° EII - Special Reinforced

(Continued)


SR Fipt x SR Fipt - Stainless Steel Collar



Part Number	Size	G	H	M	Approx. Wt. (Lbs.)
808-010CSR	1	25/32	1-11/16	1-23/32	.24
808-012CSR	1-1/4	15/16	1- 7/8	2- 1/16	.36
808-015CSR	1-1/2	1- 1/32	2- 1/8	2- 7/16	.52
808-020CSR	2	1-19/32	2- 1/2	3	.96

90° Street EII

Spigot x Socket



Part Number	Size	G	G1	H	H1	M1	Approx. Wt. (Lbs.)
809-005C	1/2	25/32	19/32	1-11/16	1-15/32	1-3/16	.07
809-007C	3/4	29/32	11/16	1-15/16	1-11/16	1-13/32	.11
809-010C	1	1-3/32	27/32	2- 7/32	2	1-23/32	.20
809-012C	1-1/4	1-5/16	1-1/32	2-9/16	2-9/32	2- 3/32	.31
809-015C	1-1/2	1- 7/16	1- 3/16	2-13/16	2- 9/16	2- 3/8	.42
809-020C	2	1- 3/4	1- 7/16	3- 1/4	2-31/32	2- 7/8	.64
809-025C ¹	2-1/2	3-3/8	1-1/2	5-1/4	3- 3/8	3-1/2	1.41
809-030C	3	2- 3/8	1-13/16	4- 1/4	3-11/16	4- 3/16	1.70
809-040C	4	3-1/32	2-9/32	5-9/32	4-9/16	5- 1/4	2.94
809-060C ¹	6	5-13/16	3-13/16	8-13/16	6-13/16	7- 9/16	9.27
809-080C ¹	8	7-1/8	5	11-1/8	8-7/8	9- 3/4	17.33
809-100C ¹	10	8-7/8	5-7/8	13-7/8	10-7/8	12- 1/16	34.95
809-100CF [*]	10	14-5/16	11-13/16	20-5/16	17-1/16	11-15/16	42.52
809-120C ¹	12	11	7	17	13	14-5/16	57.29
809-120CF [*]	12	16-5/8	13-5/8	23-5/8	19-7/8	14-1/8	74.92
809-140C ¹	14	11-1/2	7-1/2	18-1/2	14-1/2	15-9/16	70.92
809-140CF [*]	14	19-1/2	16	27-1/2	23	15-1/2	112.42
809-160CF [*]	16	22-7/16	18-7/16	31-7/16	26-7/16	17-11/16	164.40
809-180CF [*]	18	25-3/8	20-7/8	35-3/8	29-7/8	19-7/8	200.00
809-200CF [*]	20	28-5/16	23-5/16	39-5/16	33-5/16	22-1/16	294.00
809-240CF [*]	24	34-1/4	28-1/4	47-1/4	40-1/4	26-7/16	546.72