




Schedule 80 CPVC Technical Schedule 80 CPVC Fittings

Cap

Fipt

(Continued)




Part Number	Size	M	W	Approx. Wt. (Lbs.)
848-025C	2-1/2	3-11/16	2-15/32	.58
848-030C	3	4- 3/8	2- 7/16	.77
848-040C	4	5-17/32	3	1.37
848-060CF*	6	7-3/16	4-3/8	2.20
848-080CF*	8	9-3/8	4-3/8	3.76
848-100CF*	10	11-5/8	5-3/4	6.38
848-120CF*	12	13-13/16	6-3/16	10.24

* Fabricated

Cap - Special Reinforced


SR Fipt - Stainless Steel Collar



Part Number	Size	M	W	Approx. Wt. (Lbs.)
848-002CSR	1/4	27/32	27/32	.01
848-003CSR	3/8	31/32	29/32	.02
848-005CSR	1/2	1-3/16	1-1/16	.04
848-007CSR	3/4	1- 3/8	1- 3/32	.05
848-030CSR	3	4- 9/32	2- 7/16	.84

Plug

Spigot




Part Number	Size	L	Approx. Wt. (Lbs.)
849-005C	1/2	1-5/32	.03
849-007C	3/4	1- 1/4	.03
849-010C	1	1- 3/8	.06
849-012C	1-1/4	1-17/32	.10

Schedule 80 CPVC Technical
Schedule 80 CPVC Fittings



Plug
 Spigot

(Continued)




Part Number	Size	L	Approx. Wt. (Lbs.)
849-015C	1-1/2	1-11/16	.14
849-020C	2	1- 7/8	.22
849-025CF ^{4*}	2-1/2	5- 3/8	1.12
849-030CF ^{4*}	3	5-7/8	1.55
849-040CF ^{4*}	4	6-15/16	2.66
849-060CF ^{4*}	6	9-5/8	6.75
849-080CF ^{4*}	8	12-3/16	13.50
849-100CF ^{4*}	10	12-1/4	17.99
849-120CF ^{4*}	12	14-1/8	28.85
849-140CF ^{4*}	14	15-3/8	39.91
849-160CF ^{4*}	16	18	57.90
849-180CF ^{4*}	18	19-1/4	74.02
849-200CF ^{4*}	20	25-1/4	76.91
849-240CF ^{4*}	24	30-1/4	208.48

⁴ Plug fabricated using Cap and pipe spigot.

* Fabricated

Plug
 Mipt



Part Number	Size	L	Approx. Wt. (Lbs.)
850-002C	1/4	23/32	.01
850-003C	3/8	3/4	.01
850-005C	1/2	27/32	.01
850-007C	3/4	7/8	.02
850-010C	1	1- 1/16	.05
850-012C	1-1/4	1-5/16	.07
850-015C	1-1/2	1-3/8	.10
850-020C	2	1- 3/8	.16
850-025C	2-1/2	1-13/16	.29
850-030C	3	1- 7/8	.45
850-040C	4	2-1/8	.81
850-060C	6	2- 3/32	1.79
850-060CF ^{4*}	6	7-1/2	5.50
850-080C	8	2-13/32	3.53