




Schedule 40 Fittings Technical

Schedule 40 Fittings Dimensions & Information

90° EII


Fipt x Fipt



Part Number	Size	G	H	M	Approx. Wt. (Lbs.)
408-005	1/2	1/2	1- 7/32	1- 3/32	.06
408-007	3/4	17/32	1- 1/4	1- 5/16	.08
408-010	1	21/32	1-9/16	1- 5/8	.15
408-012	1-1/4	1	2	1-31/32	.25
408-015	1-1/2	1-3/16	2-5/32	2-1/4	.34
408-020	2	1- 5/16	2-3/8	2- 3/4	.48

90° Street EII

Spigot x Socket



Part Number	Size	G	G1	H	H1	M1	Approx. Wt. (Lbs.)
409-005	1/2	23/32	1/2	1- 15/32	1- 1/4	1-1/8	.04
409-007	3/4	27/32	17/32	1-27/32	1-17/32	1-11/32	.07
409-010	1	1	11/16	2-1/8	1-13/16	1- 5/8	.12
409-012	1-1/4	1-7/32	13/16	2-15/32	2- 1/16	1-31/32	.18
409-015	1-1/2	1-11/32	1- 1/16	2-21/32	2- 3/8	2- 1/4	.25
409-020	2	1-5/8	1-7/32	3	2- 5/8	2-23/32	.34
409-025	2-1/2	1-15/16	1-1/2	3-11/16	3-1/4	3-11/32	.74
409-030	3	2- 9/32	1-13/16	4- 5/32	3-11/16	4	1.08
409-040	4	2-31/32	2- 5/16	4-15/16	4-11/32	5-1/32	1.85
409-050	5	6-1/16	3-1/16	9-9/16	6-1/16	6- 1/8	4.27
409-060	6	6-9/16	3-9/16	9-9/16	6-9/16	7-1/4	5.99
409-080	8	8-1/2	4-1/2	12-1/2	8- 1/2	9-3/8	10.70
409-100F*	10	9-9/16	9-9/16	14-13/16	14-13/16	11-1/2	20.09
409-140F*	14	12-15/16	12-15/16	19-15/16	19-15/16	14- 7/8	44.65
409-160F*	16	19-1/4	15-1/4	28-1/4	23-1/4	17	74.84
409-180F*	18	21-13/16	17-5/16	31-13/16	26-5/16	19- 1/8	115.96
409-200F*	20	24-3/8	19-3/8	35-3/8	29-3/8	21- 3/16	139.78
409-240F*	24	29-7/16	23-7/16	42-7/16	35-7/16	25-3/8	238.36

* Fabricated