




Schedule 40 Fittings Technical PVC Gray Sch 40 Fittings Dimensions

Plug - Gray

Mipt




(Continued)

Part Number	Size	L	Approx. Wt. (Lbs.)
450-015G	1-1/2	1-11/32	.09
450-020G	2	1-3/8	.15
450-025G	2-1/2	1-25/32	.31
450-030G	3	1- 7/8	.38
450-040G	4	1-27/32	.72

Wye - Gray

Socket x Socket x Socket

100 psi maximum internal pressure rating @ 73°F (23°C)




Part Number	Size	G	G1	G2	H	H1	H2	L	M	M1	Approx. Wt. (Lbs.)
475-100G	10	2-13/32	14	14	7-13/32	19	19	26-13/32	11-19/32	11-19/32	26.65
475-120G	12	2-11/16	16- 1/8	16- 7/32	8- 3/4	22- 7/32	22- 9/32	31- 1/32	13-21/32	13-21/32	41.32

Union - Socket/Buna - Gray

Socket x Socket with Buna-N O-ring Seal

150 psi @ 73°F (23°C)

Dimensions Also Applicable to
497-XXXG EPDM O-Ring Seals



Part Number	Size	L	M	N	NUT O.D.	Approx. Wt. (Lbs.)
457-005G	1/2	1-27/32	1- 3/32	11/32	1-23/32	.08
457-007G	3/4	2- 3/16	1- 5/16	11/32	1-31/32	.11
457-010G	1	2- 7/16	1- 5/8	11/32	2- 3/8	.17
457-012G	1-1/4	2-29/32	1-31/32	13/32	2-11/16	.24
457-015G	1-1/2	3- 1/32	2- 1/4	3/8	3- 3/32	.32
457-020G	2	3- 9/32	2-23/32	17/32	3- 5/8	.49