




Schedule 40 Fittings Technical
PVC Gray Sch 40 Fittings Dimensions

90° EII - Gray

Socket x Socket


(Continued)



Part Number	Size	G	H	M	Approx. Wt. (Lbs.)
406-015G	1-1/2	1- 1/16	2-3/8	2- 1/4	.27
406-020G	2	1-5/16	2-11/16	2- 3/4	.37
406-025G	2-1/2	1-17/32	3-5/16	3-11/32	.71
406-030G	3	1-7/8	3-3/4	4	1.01
406-040G	4	2-13/32	4-7/16	5- 1/32	1.71
406-050G	5	3- 1/16	6-1/16	6- 5/32	3.78
406-060G	6	3-9/16	6- 9/16	7- 9/32	4.68
406-080G	8	4-13/32	8- 7/16	9- 3/8	8.85
406-100G	10	5-27/32	10-27/32	11-19/32	15.63
406-120G	12	6-15/16	12-15/16	13-11/16	25.94

90° EII - Reducing


Socket x Socket



Part Number	Size	G	G1	H	H1	M	M1	Approx. Wt. (Lbs.)
406-101G	3/4X1/2	1/2	19/32	1- 1/2	1-11/32	1- 5/16	1- 3/32	.06
406-130G	1X1/2	15/32	3/4	1-17/32	1-1/2	1-5/8	1-3/32	.11

90° EII - Gray

Socket x Fipt



Part Number	Size	G	G1	H	H1	M	Approx. Wt. (Lbs.)
407-005G	1/2	1/2	1/2	1- 1/4	1- 1/4	1- 3/32	.05
407-007G	3/4	9/16	9/16	1- 9/16	1- 9/32	1- 5/16	.08
407-010G	1	11/16	11/16	1-13/16	1- 9/16	1- 5/8	.15
407-012G	1-1/4	7/8	1-1/8	2- 1/8	2-1/16	2- 1/16	.26
407-015G	1-1/2	1	1- 1/16	2- 5/16	2	2- 1/4	.29
407-020G	2	1- 3/16	1-5/16	2-11/32	2-11/32	2-23/32	.46