



#### **Mueller Streamline Co. Headquarters**

150 Schilling Blvd  
Suite 201  
Collierville, Tennessee 38017  
United States  
Phone: 901 753 3200

#### **Mueller Streamline Co. International**

525 Okeechobee Blvd  
Suite 860  
West Palm Beach, FL 33401  
United States  
Phone: 561 273 8300

[All Categories](#) > [Copper Pressure Fittings](#) > [Couplings](#) > [Mueller Streamline® Coupling No Stop \(C x C\)](#) > Item # W 01910

---

## **ITEM # W 01910, COUPLING NO STOP, C X C, 2-1/2"**

---

Streamline® Copper Solder-Joint Fittings for supply/pressurized systems have been the leading brand of copper fittings for over 80 years. Available in both wrought copper and cast bronze, our product selection has grown to become the most extensive in the industry. We are the acknowledged experts at engineering and manufacturing precision solder-joint copper fittings. Quality, consistency and reliability have made the Streamline® brand trusted and specified all around the world.

For use in above-ground potable water supply systems

Constructed of high-grade copper or bronze materials

Made to applicable ASME standards B16.15, B16.18, B16.22, B16.24, B16.50, B1.20.1

Wrot fittings meet NSF 61G



— [less](#)

---

[Specifications](#) | [Dimensions](#) | [Details](#)

## Specifications

|                              |                                                                                    |
|------------------------------|------------------------------------------------------------------------------------|
| <b>Weight</b>                | 0.66 lb                                                                            |
| <b>Material</b>              | WROT COPPER                                                                        |
| <b>Operating Temperature</b> | <a href="#">CDA-Copper-Fitting-Pressue-Temp-Ratings</a>                            |
| <b>Operating Pressure</b>    | <a href="#">CDA-Copper-Fitting-Pressue-Temp-Ratings</a>                            |
| <b>End Type</b>              | C - Cup (Female Solder)                                                            |
| <b>End Size</b>              | 2 1/2                                                                              |
| <b>Second End Type</b>       | C - Cup (Female Solder)                                                            |
| <b>Second End Size</b>       | 2 1/2                                                                              |
| <b>Standards</b>             | NSF 61G<br>ASME B16.15<br>ASME B16.18<br>ASME B16.22<br>ASME B16.24<br>ASME B16.50 |

## Dimensions

|                       |         |
|-----------------------|---------|
| <b>Overall Length</b> | 3.13 in |
| <b>Overall Height</b> | 2.79 in |
| <b>Overall Width</b>  | 2.79 in |

## Details

|                      |          |
|----------------------|----------|
| <b>Style</b>         | WC-400NS |
| <b>Qty Pcs / Bag</b> | 1        |

|                              |                          |
|------------------------------|--------------------------|
| <b>Master Qty Pcs / Box</b>  | 50                       |
| <b>Mueller Description 1</b> | 2-1/2 C X C NO-STOP COUP |
| <b>Mueller Description 2</b> | 2-5/8 OD NO-STOP COUP    |