

45° Elbow

P x P



Job Name	<input type="text"/>
Job Location	<input type="text"/>
P.O.#	<input type="text"/>
Engineer	<input type="text"/>
Contractor	<input type="text"/>
Wholesaler	<input type="text"/>
Merit Associate	<input type="text"/>

Copper Press Small Diameter 45° Elbow is available in sizes ½" – 2" with an EPDM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring (VIPR)[™]** - facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP)** - in addition to the VIPR, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical and industrial applications.

Copper Press Operational Parameters

EPDM working pressure range from full vacuum to 300 psi for water.

Copper Press Fitting Certifications

ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.

Copper Press Codes and Standards

ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.

45° Elbow

P x P

Item Number	D1 (in)	L (in)	A (in)
EPDM			
MB11470	½"	1.10	0.30
MB11480	¾"	1.40	0.45
MB11490	1"	1.42	0.47
MB11500	1¼"	1.97	0.83
MB11510	1½"	2.30	0.85
MB11520	2"	2.44	0.83

