

**90° Drop Ear Elbow** **FTG x P**



<b>Job Name</b>	<input type="text"/>
<b>Job Location</b>	<input type="text"/>
<b>P.O.#</b>	<input type="text"/>
<b>Engineer</b>	<input type="text"/>
<b>Contractor</b>	<input type="text"/>
<b>Wholesaler</b>	<input type="text"/>
<b>Merit Associate</b>	<input type="text"/>

**Copper Press Small Diameter 90° Drop Ear Elbow FTG x P** is available in sizes 1/2" x 3/8" FPT – 3/4" x 3/4" FPT with an EPDM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring (VIPR)™** - facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP)** - in addition to the VIPR, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical and industrial applications.

**Copper Press Operational Parameters**

EPDM working pressure range from full vacuum to 300 psi for water.

**Copper Press Fitting Certifications**

ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.

**Copper Press Codes and Standards**

ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.

**90° Drop Ear Elbow** **FTG x P**

Item Number	D1 (in)	D2 (in)	L1 (in)	A1 (in)	L2 (in)	A2 (in)
<b>EPDM</b>						
MB24590	1/2"	3/8" FPT	1.77	0.94	1.36	0.59
MB24600	1/2"	1/2" FPT	1.77	0.94	1.77	0.94
MB24610	3/4"	3/4" FPT	2.13	1.18	2.13	1.18

