

90° Street Elbow **FTG x P**



Job Name	<input type="text"/>
Job Location	<input type="text"/>
P.O.#	<input type="text"/>
Engineer	<input type="text"/>
Contractor	<input type="text"/>
Wholesaler	<input type="text"/>
Merit Associate	<input type="text"/>

Copper Press Small Diameter 90° Street Elbow FTG X P is available in sizes 1/2" – 2" with an EPDM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring (VIPR)[™]** - facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP)** - in addition to the VIPR, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical and industrial applications.

Copper Press Operational Parameters

EPDM working pressure range from full vacuum to 300 psi for water.

Copper Press Fitting Certifications

ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.

Copper Press Codes and Standards

ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.

90° Street Elbow **FTG x P**

Item Number	D1 (in)	L1 (in)	A (in)	L2 (in)
EPDM				
MB11350	1/2"	1.56	0.75	1.73
MB11360	3/4"	2.03	1.08	2.13
MB11370	1"	2.24	1.30	2.36
MB11380	1 1/4"	2.64	1.50	2.93
MB11390	1 1/2"	3.23	1.77	3.54
MB11400	2"	3.98	2.17	4.29

