

Carbon XL 90° Street Elbow

FTG x Press



Job Name	
Job Location	
P.O.#	
Engineer	
Contractor	
Wholesaler	
Merit Associate	

- MeritPress™ - Carbon XL 90° Street Elbow FTG x Press** is available in sizes 2½" – 4" with an EPDM, HNBR or FKM sealing element.
- **FIRST TO MARKET Visual Indicator Press Ring (VIPR)™:** facilitates immediate identification of un-pressed connections.
 - **Leak Before Press (LBP):** in addition to the Visual Indicator Press Ring (VIPR)™, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
 - **Surface Protection:** Corrosion Resistant Zn-Ni Plating.
 - **Grab Ring:** Deforms and Grips Outside Diameter of Pipe.
 - **Applications:** Hydronic Heating, the Conveyance of Fluids, Gases, Oils, and Low-Pressure Steam.

MeritPress™ - Carbon Press Operational Parameters
Working pressure range from full vacuum to 250 psi (17.2 bar) for water, 125 psi (8.6 bar) for gas, and 200 psi (13.7 bar) for industrial applications.

MeritPress™ - Carbon Press Certifications
IAPMO Z 1117 (EPDM and FKM), IAPMO/ANSI LC 4/CSA 6.32 (HNBR), and UL 213 and FM 1920 (EPDM & FKM).

MeritPress™ - Carbon Press Codes and Standards
IAPMO Z 1117, IAPMO/ANSI LC 4/CSA 6.32, ASME B31.1, B31.3, B31.9, CSA B149.1, UPC, and UMC.

Carbon XL 90° Street Elbow

FTG x Press

Item Number			Nominal Size 1	A (in)	L (in)	L1 (in)
EPDM	HNBR	FKM				
MB90525	MB90526	MB90527	2½"	4.09	5.98	5.98
MB90530	MB90531	MB90532	3"	4.80	7.09	6.97
MB90535	MB90536	MB90537	4"	6.10	9.25	9.06

