

**Carbon 45° Elbow**

P x P



<b>Job Name</b>	<input type="text"/>
<b>Job Location</b>	<input type="text"/>
<b>P.O.#</b>	<input type="text"/>
<b>Engineer</b>	<input type="text"/>
<b>Contractor</b>	<input type="text"/>
<b>Wholesaler</b>	<input type="text"/>
<b>Merit Associate</b>	<input type="text"/>

**MeritPress™ - Carbon 45° Elbow P x P** is available in sizes ½" – 2" with an EPDM, HNBR or FKM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring (VIPR)™:** facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP):** in addition to the Visual Indicator Press Ring (VIPR)™, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Surface Protection:** Corrosion Resistant Zn-Ni Plating.
- **Grab Ring:** Deforms and Grips Outside Diameter of Pipe.
- **Applications:** Hydronic Heating, the Conveyance of Fluids, Gases, Oils, and Low-Pressure Steam.

**MeritPress™ - Carbon Press Operational Parameters**

Working pressure range from full vacuum to 250 psi (17.2 bar) for water, 125 psi (8.6 bar) for gas, and 200 psi (13.7 bar) for industrial applications.

**MeritPress™ - Carbon Press Certifications**

IAPMO Z 1117 (EPDM and FKM), IAPMO/ANSI LC 4/CSA 6.32 (HNBR), and UL 213 and FM 1920 (EPDM & FKM).

**MeritPress™ - Carbon Press Codes and Standards**

IAPMO Z 1117, IAPMO/ANSI LC 4/CSA 6.32, ASME B31.1, B31.3, B31.9, CSA B149.1, UPC, and UMC.

**Carbon 45° Elbow**

P x P

Item Number			Nominal Size 1	A (in)	L (in)
EPDM	HNBR	FKM			
MB90540	MB90541	MB90542	½"	0.87	1.89
MB90545	MB90546	MB90547	¾"	1.00	2.19
MB90550	MB90551	MB90552	1"	1.16	2.52
MB90555	MB90556	MB90557	1¼"	1.43	3.23
MB90560	MB90561	MB90562	1½"	1.54	3.41
MB90565	MB90566	MB90567	2"	1.87	3.80

