## Carbon XL Coupling with Stop — P x P



| | |
|---|---|
| Job Name | |
| Job Location | |
| P.O.# | |
| Engineer | |
| Contractor | |
| Wholesaler | |
| Merit Associate | |

**MeritPress™ - Carbon XL Coupling with Stop P x P** is available in sizes 2½" – 4" with an EPDM, HNBR and FKM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring (VIPR)™:** facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP):** in addition to the Visual Indicator Press Ring (VIPR)™, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Surface Protection:** Corrosion Resistant Zn-Ni Plating.
- **Grab Ring:** Deforms and Grips Outside Diameter of Pipe.
- **Applications:** Hydronic Heating, the Conveyance of Fluids, Gases, Oils, and Low-Pressure Steam.

**MeritPress™ - Carbon Press Operational Parameters**
Working pressure range from full vacuum to 250 psi (17.2 bar) for water, 125 psi (8.6 bar) for gas, and 200 psi (13.7 bar) for industrial applications.

**MeritPress™ - Carbon Press Certifications**
IAPMO Z 1117 (EPDM and FKM), IAPMO/ANSI LC 4/CSA 6.32 (HNBR), and UL 213 and FM 1920 (EPDM & FKM).

**MeritPress™ - Carbon Press Codes and Standards**
IAPMO Z 1117, IAPMO/ANSI LC 4/CSA 6.32, ASME B31.1, B31.3, B31.9, CSA B149.1, UPC, and UMC.

## Carbon XL Coupling with Stop — P x P

| Item Number | | | Nominal Size 1 | A (in) | L (in) |
|---|---|---|---|---|---|
| EPDM | HNBR | FKM | | | |
| MB90030 | MB90031 | MB90032 | 2½" | 1.18 | 4.92 |
| MB90035 | MB90036 | MB90037 | 3" | 1.42 | 5.98 |
| MB90040 | MB90041 | MB90042 | 4" | 1.63 | 7.87 |

