



Steel Male x Compression Couplings


These couplings are intended for temporary repair on cold water lines.
Do not use on hot water, steam, oxygen, petroleum or similar explosive or combustible mediums.
No pressure rating.




PART NUMBER	IPS
2950	1/2"
2951	3/4"

Steel Compression Couplings

These couplings are intended for temporary repair on cold water lines.
Do not use on hot water, steam, oxygen, petroleum or similar explosive or combustible mediums.
No pressure rating.




PART NUMBER	IPS	LENGTH
2900	1/2"	2-5/8"
2901	3/4"	2-3/4"
2902	1"	3-1/8"
2903	1-1/4"	3-1/4"
2904	1-1/2"	3-3/8"
2905	2"	3-5/8"



PART NUMBER	IPS	LENGTH
2908	1/2"	3-3/4"
2909	3/4"	4"
2910	1"	4-1/4"
2911	1-1/4"	4-3/4"
2912	1-1/2"	5"
2913	2"	5-3/8"

Brass Compression Couplings

These couplings are intended for temporary repair on cold water lines.
Do not use on hot water, steam, oxygen, petroleum or similar explosive or combustible mediums.
Maximum operating pressure is 125 PSI



PART NUMBER	CWT	IPS	LENGTH
2916	1/2"	3/8"	2-9/16"
2917	3/4"	1/2"	2-3/4"
2918	1"	3/4"	3"
2919	1-1/4"	1"	3"
2920	1-1/2"	1-1/4"	3-1/4"



PART NUMBER	CWT	IPS	LENGTH
2921	1/2"	3/8"	5"
2922	3/4"	1/2"	5"
2923	1"	3/4"	5"
2924	1-1/4"	1"	5"
2925	1-1/2"	1-1/4"	5"
2926	2"	—	5"
2929	—	1-1/2"	5"
2930	—	2"	5"

Pressure rating of 125 PSI