



Heavy Duty No-Hub Couplings

PASCO No-Hub couplings utilize the unique “High Efficiency” (HE) clamp specifically developed for no-hub installations. This HE clamp offers the most band load in the industry when 80 lbs. of installation torque is applied.

- 304 Stainless Steel
- Comply with ASTM C1540
- Conform to CISPI 310
- Additional clamps provide better sealing and load distribution
- 5/16” Hex head screws



• Use **PASCO 2SM**

PART NUMBER	SIZE
PNHC-1.5HD	1-1/2"
PNHC-2HD	2"
PNHC-3HD	3"
PNHC-4HD	4"
PNHC-6HD	6"
PNHC-8HD	8"
PNHC-10HD	10"

No-Hub Couplings

PASCO No-Hub couplings utilize the unique “High Efficiency” (HE) clamp specifically developed for no-hub installations. This HE clamp offers the most band load in the industry when 60 lbs. of installation torque is applied.

- AISI 301 stainless steel band and shield.
- AISI 305 stainless steel screw
- Gaskets conform to ASTM C564
- Complies with standards:
- CSA B70-M91
- CSA B602-M90
- CISPI 310-95
- ASTM C1277



• Use **PASCO 2SH**

PART NUMBER	SIZE
PNHC-1.5	1-1/2"
PNHC-2	2"
PNHC-21.5	2" x 1-1/2"
PNHC-3	3"
PNHC-32	3" x 2"
PNHC-4	4"
PNHC-43	4" x 3"
PNHC-5	5"
PNHC-6	6"
PNHC-8	8"
PNHC-10	10"
PNHC-12	12"